PRODUCT INFORMATION



SYNTEKO NEWSHINE



1696

Synteko NEWSHINE is a waterborne maintenance product which both renews the shine and protects finished wood floors.

AREA OF USE: for periodic maintenance of wooden floors treated with Synteko finishes, especially in high-traffic areas

PRODUCT PROPERTIES:

- practically odourless
- helps protect the floor
- leaves a protective film which will help maintain the beautiful look of the floor for a longer period
- can also be used to repair light scratches
- can be applied several times without a thick layer building up
- subsequent treatment or polishing are not necessary

COVERAGE:

50 m²/ l

TOOLS:

- moist floor mop
- non-flocculent cloth
- clean tools with water immediately after use

TECHNICAL DATA:

| Base material | Waterborne acrylic dispersion |
|----------------|---|
| Solids content | Approx. 11% |
| Density | Approx. 1100 kg/m3 (9,18 lb/gal US) (11,02 lb/gal UK) |
| рН | Approx. 8,5 |
| Drying time | Approx. 30 minutes |
| Gloss | Approx. 50 (measured at 60°) |
| Self life | 36 months in unopened container from production date (s. package) |
| Storage | Store frost free. Must be stored between +5°C and +30°C (+40°F +86°F) |
| Package size | 1L |

DIRECTIONS FOR USE

- 1. Before applying Synteko NEWSHINE make sure that the floor is clean.
- 2. Sweep, mop or vacuum the floor.
- 3. Old soap, grease, polish etc. should be removed by washing with water and Synteko REMOVER.
- 4. Apply Synteko NEWSHINE in a thin, even layer using a damp mop or a non-flocculent cloth.
- 5. Leave the floor to dry for app. 30 minutes before walking on it.

HEALTH & SAFETY INFORMATION

Safety data sheet available for professional user on request. Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet), available on www.synteko.com. The following only represents a selection of important information. **Note:** Keep out of reach of children. If swallowed, seek medical advice immediately and show this container or label.

Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to fauts and defects inone of the products manufactured by us.

Producer: Sika Estonia OÜ, Estonia www.synteko.com

Date: 29.07.2014